Technical Datasheet



NDC BLACK BITUMINOUS PAINT / BLACK JAPAN PAINT

PRODUCT DESCRIPTION:

NDC BLACK BITUMINOUS PAINT is bitumen and solvent based coating which Provides an excellent economical anti-corrosive and protective coating solution for Wide range of application. It provides a weather protective and waterproofing coat for Ferrous metal surfaces.

USES:

Our Black Bituminous paint has wide range of application of common building materials especially iron, steel, timber and concrete including; Rainwater gutters and down pipes, manhole covers, corrugated sheets, fencing, storage tanks, water meter covers, etc.

SURFACE PREPARATION:

As with all surface coating, preparation of the surface is of great importance & will influence the degree of adhesion obtained & the life of the coating. All surfaces must be sound, stable, Rust free and thoroughly clean & dry.

APPLICATION:

By soft bristle brush, spray or roller.

COVERAGE & DRYING:

Coverage depends on the porosity of the surface. Plain and smooth surface 10-12 Square meter per liter.

DRYING TIME:

Drying time of the film depends on weather condition and film thickness. Heavy application will result in extended drying time. However, normally surfaces are touch dry in 3-4 hours And can be over coated after 48 hours.

THINNER:

If required use NDC Special thinner for Black Bituminous Paint.

DISCLAIMER: The information given in this data sheet is best of our knowledge, observed while tested in ideal condition in our laboratory.

WORKS: POST & VILL & PO: BAMUNARI, NH -2, DELHI ROAD .DIST HOOGHLY, 712205,

WEST BENGAL. PHONE: 9830317320

OFFICE: JEEVAN NIWAS, 30A, BLOCK -R, NEW ALIPORE, 2ND FLOOR, FLAT A/5

KOLKATA: 700 053,

CONTACT: +91 9830848300 / 98308 49200 / 9674129944.